

Specification

Nominal Voltage	2V	
Capacity(10HR)	200.0AH (1.8V/cell,20°C)	
Dimension	Length	103±2mm (4.06 inches)
	Width	206±3mm (8.11 inches)
	Container Height	355±3mm (13.98 inches)
	Total Height (with Terminal)	410±3mm (16.14 inches)
	Without Electrolyte	12.9 kg (28.44lbs)
Approx Weight	With Electrolyte 17.4 kg (38.37lbs)	
Container Material	SAN transparent container	
Rated Capacity	200.0 AH/20.0A	(10hr, 1.80V/cell, 20°C/68°F)
	177.5 AH/35.5A	(5hr, 1.75V/cell, 20°C/68°F)
	154.2 AH/51.4A	(3hr, 1.75V/cell, 20°C/68°F)
	114.2 AH/114.2A	(1hr, 1.60V/cell, 20°C/68°F)
Max. Discharge Current	1600A (5s)	
Internal Resistance	Approx 0.95mΩ	
Operating Temp. Range	Discharge	-15~55°C (5~131°F)
	Charge	0~45°C (32~113°F)
	Storage	-15~45°C (5~113°F)
Type and number of poles	M8	
Charging	Floating voltage: 2.23V~2.25V at 20°C(68°F)Temp.	
	Boost charge: 2.30V~2.40V at 20°C(68°F)Temp.	
	Charging current(max.): 0.1CA	
	Temp. Coefficient -3mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge (4% per month)	PS OPzS batteries may be stored for up to 6 months at 20°C(68°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ Telecommunications.
- ◆ Radio and cellular telephone relay stations.
- ◆ Emergency lighting systems.
- ◆ Power stations, Conventional power stations,
- ◆ Alternative power (solar, wind).
- ◆ Large UPS and computer back-up.
- ◆ Railway signalling.
- ◆ Maritime standby power on ships and ashore.
- ◆ Standby power.
- ◆ Buoy lighting.
- ◆ Long service life, designed life 15-20 years.

Constant Current Discharge (Amperes) at 20 °C (68°F)

F.V/Time	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V/cell	151.6	131.7	114.2	90.0	74.4	55.6	44.7	37.8	32.7	25.9	21.4	11.6
1.65V/cell	142.4	126.7	110.4	87.7	72.7	54.7	44.1	37.3	32.3	25.6	21.1	11.5
1.70V/cell	135.2	119.5	106.2	84.9	71.0	53.1	43.1	36.5	31.7	25.1	20.8	11.3
1.75V/cell	126.8	113.9	100.8	80.9	68.0	51.4	41.8	35.5	30.9	24.7	20.4	11.1
1.80V/cell	112.8	102.7	92.8	75.9	63.9	48.8	40.0	34.1	29.8	24.0	20.0	10.9
1.85V/cell	90.0	85.1	79.4	67.5	58.0	44.7	37.0	31.9	28.0	22.8	19.1	10.5


Constant Power Discharge (Watts) at 20 °C (68°F)

F.V/Time	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V/cell	258.8	230.5	202.8	161.8	135.3	101.8	82.6	70.3	61.3	48.7	40.4	22.0
1.65V/cell	248.4	224.3	197.6	158.5	132.9	100.6	81.8	69.7	60.7	48.3	40.1	21.9
1.70V/cell	239.0	213.8	191.6	154.5	130.3	98.2	80.2	68.5	59.8	47.7	39.6	21.7
1.75V/cell	228.0	205.9	183.5	148.3	125.7	95.7	78.2	67.0	58.5	47.0	39.1	21.4
1.80V/cell	205.5	188.5	171.1	140.6	119.2	91.5	75.3	64.5	56.7	46.0	38.5	21.1
1.85V/cell	166.8	158.4	148.6	126.7	109.4	84.7	70.4	61.0	53.8	44.1	37.1	20.5


Specifications subject to change without notice.

Dimensions


Terminal




Discharge Characteristics




Charge voltage Vs ambient temperature curve




Discharge capacity Vs Ambient temperature curve (I10A)



Relation curves of service life and ambient temperature



Self Discharge Characteristics



- A** No supplementary charge required (Carry out supplementary charge before use if 100% capacity is required.)
- B** Supplementary charge required before use. Optional charging way as below:
 1. Charged for above 3 days at limited current 0.1CA and constant voltage 2.25V/cell.
 2. Charged for above 20hours at limited current 0.1CA and constant voltage 2.45V/cell.
 3. Charged for 8~10hours at limited current 0.05CA .
- C** Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this is reached.

POWER-SONIC

CORPORATE OFFICE • 7550 Panasonic Way • San Diego, CA 92154 • USA • Tel: +1-619-661-2020 • Fax: +1-619-661-3650

www.power-sonic.com